



Item # _____

Job _____

SUPER ERECTA SHELF® PRINTED CIRCUIT BOARD TRUCKS HORIZONTAL HOLD

- **Safe PCB Handling:** Metro PCB Trucks safely transport and store large circuit boards – or large quantities of small boards.
- **Two Sizes Available:** Trucks come in two lengths – 36" (910mm) and 48" (1220mm). Both models are 24" (610mm) wide.
- **High Density Storage:** Trucks provide 48 levels for circuit boards and offer $1\frac{1}{16}$ " (17mm) spacing for high density loading. Middle panel has extrusions on both sides. Slides accept boards up to $22\frac{1}{2}$ " (570mm) long and up to $\frac{1}{2}$ " (13mm) thick.
- **Adjustable:** Panels slide along side frames to the exact width of boards. Holding knobs at each panel corner are manually tightened to hold panels securely in place. To accommodate boards from 3" (75mm) to $22\frac{1}{2}$ " (570mm) deep, the vertical stop bar on the face of each panel can be placed in any location along the face of the panel.
- **Versatile:** Ideal for circuit board curing operations (if over 160°F [70°C], Hi Temp. Kit must be specified) as well as handling large quantities of unpopulated or populated boards.
- **Conductive:** All metal truck components eliminate electrostatic build-up in properly grounded units. Slides are natural finish extruded aluminum.
- **Super Erecta Shelf Construction:** Provides fast, secure assembly of unit without special tools.
- **Identifiable:** Numbering strip is standard for easy identification of storage levels.



SUPER ERECTA SHELF®
Printed Circuit Board Trucks

Vertical & Horizontal Hold

51.04



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



SUPER ERECTA SHELF® PRINTED CIRCUIT BOARD TRUCKS HORIZONTAL HOLD

Specifications

- **Panels:** Natural finish extruded aluminum.
- **Frames:** Structural chrome-plated steel with tapered corner collars which attach to the posts via aluminum split sleeves and retaining rings, making it possible to position the panel/frame unit at the desired working level.
- **Load Rating:** 5 lbs. (2kg) per slide, 75 lbs. (34kg) per bay, 150 lbs. (68kg) maximum per unit.

Dimensions

| Cat. No. | Width | | Length | | Height | | Maximum Board Size without Center Panel | | Capacity Full-Size Boards | Capacity | Capacity | Approx. Pkd. Wt. | |
|----------|-------|------|--------|------|--------|------|---|------------|---------------------------|---|---|------------------|------|
| | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | | 11" (275mm) Boards without Center Panel | 11" (275mm) Boards with 2 Center Panels | (lbs.) | (kg) |
| CBL536BC | 24 | 610 | 36 | 910 | 68 | 1727 | 22 ¹ / ₂ x 30 ¹ / ₄ | 517 x 770 | 48 | 96 | 192 | 105 | 48 |
| CBL556BC | 24 | 610 | 48 | 1220 | 68 | 1727 | 22 ¹ / ₂ x 42 ¹ / ₄ | 517 x 1075 | 48 | 96 | 192 | 120 | 54 |

Accessories

Center Panel Assembly (Offered as standard with each unit and as an accessory).

| Cat. No. | Width | | Length | | Height | | Approx. Pkd. Wt. | |
|----------|--------------------------------|------|--------------------------------|------|-------------------------------|------|------------------|------|
| | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | (lbs.) | (kg) |
| CBLP2 | 23 ¹ / ₂ | 600 | 37 ¹ / ₄ | 945 | 1 ⁵ / ₈ | 41 | 24 | 11 |

Other Accessories

| Cat. No. | Description | Approx. Pkd. Wt. | |
|----------|--|------------------|------|
| | | (lbs.) | (kg) |
| HTK-I | High Temperature Kit (Includes 4 high temperature casters (two with brakes), two "Caution Hot" labels, and 4 metal post caps. Required for temperatures over 160°F [70°C]. Kit good to 400°F [205°C]). | 13 | 6 |
| IDK-IL | Label Identification Kit (contains two labels). | | |

SUPER ERECTA SHELF®
PRINTED CIRCUIT BOARD TRUCKS
VERTICAL HOLD



SUPER ERECTA SHELF®
PRINTED CIRCUIT BOARD TRUCKS
VERTICAL HOLD

- **Safe PCB Handling:** Metro PCB Trucks safely transport and store large circuit boards – or large quantities of small boards.
- **Two Sizes Available:** Trucks come in two lengths – 36" (910mm) and 48" (1220mm). Both models are 24" (610mm) wide.
- **High Density Storage:** Trucks provide 80-112 slots for circuit boards and offer $1\frac{1}{32}$ " (9mm) spacing for high density loading. Slides accept boards up to 23" (582mm) long and up to $\frac{3}{16}$ " (5mm) thick.
- **Adjustable:** Bottom panel is held stationary on posts while top panel adjusts vertically. Bottom panel has a stop bar on front and back.
- **Versatile:** Ideal for circuit board curing operations (if over 160°F [70°C], Hi Temp. Kit must be specified) as well as handling large quantities of unpopulated or populated boards.
- **Conductive:** All metal truck components eliminate electrostatic build-up in properly grounded units. Slides are natural finish extruded aluminum.
- **Super Erecta Shelf Construction:** Provides fast, secure assembly of unit without special tools.
- **Identifiable:** Numbering strip is standard for easy identification of storage levels.



Job _____

SUPER ERECTA SHELF®
 PRINTED CIRCUIT BOARD TRUCKS
 VERTICAL HOLD



Specifications

- **Panels:** Natural finish extruded aluminum.
- **Frames:** Structural chrome-plated steel with tapered corner collars on bottom panel frame which attach to the posts via aluminum split sleeves and retaining rings, making it possible to position the panel/frame unit at the desired working level.
- **Load Rating:** 200 lbs. (91kg) max. per bay or not to exceed 600 lbs. (272kg) per unit.

Dimensions

| Cat. No. | Width | | Length | | Height | | Maximum Board Width | | Capacity Full-Size Boards | Approx. Pkd. Wt. | |
|----------|-------|------|--------|------|--------|------|---------------------|------|---------------------------|------------------|------|
| | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | (in.) | (mm) | | (lbs.) | (kg) |
| CBV536BC | 24 | 610 | 36 | 910 | 69 | 1753 | 23 | 582 | 80 | 80 | 40 |
| CBV556BC | 24 | 610 | 48 | 1220 | 69 | 1753 | 23 | 582 | 112 | 112 | 51 |

Accessories

| Cat. No. | Description | Approx. Pkd. Wt. | |
|----------|--|------------------|------|
| | | (lbs.) | (kg) |
| HTK-I | High Temperature Kit (Includes 4 high temperature casters (two with brakes), two "Caution Hot" labels, and 4 metal post caps. Required for temperatures over 160°F [70°C]. Kit good to 400°F [205°C]). | 13 | 6 |
| IDK-IV | Label Identification Kit (contains two labels). | | |

Manufactured by:



InterMetro Industries Corporation
 North Washington Street, Wilkes-Barre, PA 18705
 Phone: 570-825-2741 • Fax: 570-825-2852
 For Product Information Call: 1-800-433-2232
 Visit Our Web Site: www.metro.com

L02-132A
 Rev. 9/00
 Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

